

Fracture

RUNNING LINE

CARPET SPECIFICATIONS

CONSTRUCTION	Infinity
PILE FIBER	100% SDN
GAUGE	1/10
STITCH RATE	16
PILE HEIGHT	0.188
TUFTED PILE WEIGHT	36
DYE METHOD	SOLUTION
PRIMARY BACKING	WOVEN POLYPROPYLENE
SECONDARY BACKING	ACTION BAC
WIDTH IN FT.	12' 0"
DENSITY FACTOR	6,902
WEIGHT DENSITY FACTOR	248,459
WARRANTY	TEN YEAR LIMITED WEAR
SOIL & STAIN TREATMENT	SCOTCHGARD & STAIN RELEASE AVAILABLE
PATTERN REPEAT	24" x 80"
CERTIFICATION	CARPET & RUG INSTITUTE GLP 2121
TESTING DATA	ASTM E-648 Flooring Radiant Panel: Class I
	DOC-FF1-70 Methenamine Pill Test: Passes
	AATCC 134 Electrostatic Propensity: Less than 3.5 KV
	E-622 Smoke Chamber: Less than 450

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and /or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

This carpet is manufactured and recommended for floor covering use only. As in all quality carpet, colors are subject to dye lot variations. For optimum side match and finished seam appearance, this product should be installed whenever possible, with seams running perpendicular to major external (outside) light sources.

The equipment used to manufacture patterned (graphics) carpet may create visible lines in both length and width directions. This characteristic will not always be detectable in small samples and is not considered a manufacturing defect.

As with all patterned carpets, perfect pattern match may not be obtainable

at seams. Tolerances in pattern registration – bow and skew – are to be expected. Reasonable pattern matches may be obtained by using trained, experienced professional installers and by following the manufacturers' installation procedures. Chair pads are recommended under office chairs with rollers to preserve appearance retention, avoid premature or accelerated wear, and act as a deterrent toward delamination. Special backing systems are available that do not require chair pads.

Walk off mats are recommended at building entry ways to reduce soiling. Recommended adhesive is Signature Hospitality 2800 Multi Purpose Latex Adhesive and Signature Hospitality 1801 Universal Seam Sealer. For Warranties to apply, all adhesives and seam sealers must be approved by Signature Hospitality Carpet.

For samples, specifications, or other information please contact your sales representative.

SIGNATURE

2222 South Hamilton Street • Dalton, GA 30721
P.O. Box 1328, Dalton, GA 30722-1328
1.800.809.7086 • T 706.270.5799 • F 706.270.8779
info@signaturehospitalitycarpet.com
www.signaturehospitalitycarpets.com