

PRODUCT SPECIFICATION

STYLE	90 DEGREES
CONSTRUCTION	PATTERNED LOOP
BACKING	RIGHT ANGLE MODULAR
DYE METHOD	SOLUTION DYED
FIBER TYPE	SD NYLON
FACE WEIGHT	20 OZ
PILE DENSITY	6000
FINISH PILE THICKNESS	0.12
PATTERN REPEAT	N/A
GAUGE	1/12
STANDARD SIZE	24" X 24"

TESTING


RADIANT PANEL	CLASS I (ASTM-E-648)
SMOKE DENSITY	<450 (ASTM E-662)
STATIC CONTROL	3.5 kv (AATCC-134)
ANTIMICROBIAL	PASSES (AATCC-174)

THIS PRODUCT MEETS THE GUIDELINE AS SET FORTH IN THE AMERICANS WITH DISABILITIES ACT FOR MINIMUM STATIC COEFFICIENT OF FRICTION OF 0.6 FOR ACCESSIBLE ROUTES.

ENVIRONMENTAL CERTIFICATION

INDOOR AIR QUALITY	GLP0070
--------------------	---------

INSTALLATION METHODS



RECOMMENDED ADHESIVES

SIGNATURE MODULAR ADHESIVE

WARRANTIES

LIFETIME PERFORMANCE FOR WEAR
LIFETIME FIBER PERFORMANCE FOR STATIC
LIFETIME STAIN REMOVAL
LIFETIME COLOR FASTNESS TO LIGHT AND ATMOSPHERIC CONTAMINANTS
LIFETIME FOR TUFT BIND STRENGTH (EDGE RAVEL, YARN PULLS, ZIPPERING)
LIFETIME AGAINST DELAMINATION



2222 S Hamilton Street
Dalton, Georgia 30721
PH: 800.809.7086, FAX: 706.270.8779
www.signaturecarpets.com