

# Domaine

## CARPET SPECIFICATIONS

CONSTRUCTION	1/10 INFINITY TIP SHEAR
PILE FIBER	100% SOLUTION DYED NYLON
STITCH RATE	14.5 SPI
PILE HEIGHT	.218
TUFTED PILE WEIGHT	32 oz
DYE METHOD	SOLUTION
PRIMARY BACKING	WOVEN POLYPROPYLENE
SECONDARY BACKING	ACTIONBAC
WIDTH	12'
DENSITY FACTOR	5,284
WEIGHT DENSITY FACTOR	169,088
WARRANTY	TEN YEAR LIMITED WEAR
SOIL & STAIN TREATMENT	SCOTCHGARD
PATTERN REPEAT	24" W x 42" L
CERTIFICATION	CARPET & RUG INSTITUTE GLP5076
TESTING DATA	ASTM E-648 Flooring Radiant Panel: Class I DOC-FF1-70 Methenamine Pill Test: Passes AATCC 134 Electrostatic Propensity: Less than 3.5 KV E0622 Smoke Chamber: Less than 450

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and /or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

This carpet is manufactured and recommended for floor covering use only. As in all quality carpet, colors are subject to dye lot variations. For optimum side match and finished seam appearance, this product should be installed whenever possible, with seams running perpendicular to major external (outside) light sources.

The equipment used to manufacture patterned (graphics) carpet may create visible lines in both length and width directions. This characteristic will not always be detectable in small samples and is not considered a manufacturing defect.

As with all patterned carpets, perfect pattern match may not be obtainable at seams. Tolerances in pattern registration – bow and skew – are to be

expected. Reasonable pattern matches may be obtained by using trained, experienced professional installers and by following the manufacturers' installation procedures.

Chair pads are recommended under office chairs with rollers to preserve appearance retention, avoid premature or accelerated wear, and act as a deterrent toward delamination. Special backing systems are available that do not require chair pads.

Walk off mats are recommended at building entry ways to reduce soiling. Recommended adhesive is Signature Hospitality 2800 Multi Purpose Latex Adhesive and Signature Hospitality 1801 Universal Seam Sealer. For warranties to apply, all adhesives and seam sealers must be approved by Signature Hospitality Carpet.

For samples, specifications, or other information please contact your sales representative.

# SIGNATURE

2222 South Hamilton Street • Dalton, GA 30721  
P.O. Box 1328, Dalton, GA 30722-1328  
1.800.809.7086 • T 706.270.5799 • F 706.270.8779  
info@signaturehospitalitycarpet.com  
www.signaturehospitalitycarpets.com